Dynamic Graphics in a GIS: A Bidirectional Link between ArcView 2.0™ and XGobi

Jürgen Symanzik[1], **James J. Majure**[2], **Dianne Cook**[1]

[1] Department of Statistics, Iowa State University, Ames, IA 50011, USA

[2] GIS Support and Research Facility, Iowa State University

symanzik@iastate.edu

Abstract. In Symanzik et al. (1994) we have presented a link between a Geographic Information System (GIS), ARC/INFO™, and an interactive dynamic graphics program, XGobi. So far, that link was only unidirectional and allowed the transfer of data from ARC/INFO into XGobi, but not vice versa.

Meanwhile, ESRI, the publisher of ARC/INFO, has released ArcView 2.0™, a package based on ARC/INFO. ArcView 2.0 allows calls to external procedures via Remote Procedure Calls (RPCs) and it also enables external programs to invoke ArcView 2.0 functions using RPCs. These features enable us to provide a bidirectional link between ArcView 2.0 and XGobi. Our link now combines the dynamic, interactive strengths of XGobi for visualizing high dimensional data with the map handling tools of ArcView 2.0, specifically to explore spatial data. This paper presents information about the technical realization of the link and it addresses substantial questions such as security and concurrency issues.

1 Introduction

Interactive dynamic graphics programs have proven their usefulness for the exploration of high–dimensional data. When those data are collected at spatial locations, it becomes necessary to include the locations as part of the analysis. This leads very naturally to the integration of a Geographic Information System (GIS), to be used for the display of spatial locations and concomitant geographic variables, with a dynamic graphics program, to visualize and explore the corresponding data space. This type of link has been constructed between ArcView 2.0, a GIS, and XGobi (Swayne et al., 1991), an interactive dynamic graphics program in the X Window System™ environment.

This work is preceeded by Symanzik et al. (1994), in which a unidirectional link between the GIS ARC/INFO and XGobi is described. The subsequent release of ArcView 2.0 has provided both a more appropriate environment in which to implement the link, as well as technical solutions to the implementation of the link in both directions via Remote Procedure Calls (RPCs).

We will start in Section 2 with motivation for why a link like this is desirable and a description of the type of tools that are made available. Section 3 will describe the technical realization of our bidirectional link using RPCs. Security and concurrency issues related to the link will be discussed in Section 4. An example of how this type of link can be put to use will be given in Section 5. We will conclude by describing possibilities for future work.

2 Integration of Interactive and Dynamic Graphics Tools into a GIS

Integrating a GIS with a dynamic graphics program is only one approach for including spatial locations in graphical analyses, though we feel it is an important one. In this integration approach, the ability to keep sample locations in their geographic context is considered paramount. Often, concomitant geographic variables can provide information that location alone can not provide. For example, two sets of locations might be separated by a mountain range resulting in subtle changes in the collected data. If the analyst can see clearly the geographic division in sample locations, further exploratory analysis might reveal the difference in the data.

A link between a GIS and a dynamic graphics program is intended to provide functionality that is not provided separately by the GIS or the dynamic graphics program alone. While GISs provide sophisticated capabilities for the input of spatial data, its management (storage & retrieval) and the display of maps, graphics, and tables, their capability for statistical analysis is generally limited and dynamic graphical analysis is nonexistent. Recently, some suggestions have been made to redress this imbalance (e. g., Openshaw, 1991; Anselin and Getis, 1992; Ding and Fotheringham, 1992; Fotheringham and Rogerson, 1993), while others have incorporated some dynamic graphics tools into systems that lack the full features and flexibility of a GIS (e. g., Haslett et al., 1991). Although most dynamic graphics programs can plot the coordinates of spatial locations, they do not have the capabilities of producing high quality maps that provide a geographic frame of reference. Together, then

™*ARC/INFO* is a trademark of Environmental Systems Research Institute, Inc.

™*ArcView 2.0* is a trademark of Environmental Systems Research Institute, Inc.

™*X Window System* is a trademark of MIT.

ArcView 2.0 and XGobi share their strengths and produce a product that is more than the sum of the parts.

The specific tools made available by the link include the resident capabilities of both ArcView 2.0 and XGobi, as well as the ability to do linked glyph and color brushing between the two systems. The capabilities of ArcView 2.0 include the display and manipulation of sample locations and other geographic information. XGobi provides an array of graphic options including univariate and bivariate plots, three dimensional rotation, higher dimensional rotation through the grand tour, and projection pursuit. The link allows the analyst to brush points, in either ArcView 2.0 or XGobi, with a color and a glyph and to see where the corresponding points are located in the other application. Thus, outliers in an XGobi plot can be brushed to see where they were collected, or a spatial region in ArcView 2.0 can be brushed to see where the corresponding attribute measurements fall in the data space. The link also allows the user to clone the XGobi window. Under cloning we understand that a new XGobi process is started in a new window where the same data and external resources are immediately available. This enables the analyst to proceed with the exploratory analysis in the new window while the old view is still present in the old window and may be processed differently. Together, these tools provide a powerful and flexible environment for the graphical analysis of spatial data.

Additional tools have been envisioned as well. Cook et al. (1994) discussed some tools for detecting spatial dependencies, focusing on ideas related to canonical correlation analysis. Majure (1995) proposes a dynamic graphical environment for the exploration of multivariate spatial dependencies. The technology that supports the link described here is also being used to estimate and visualize spatial cumulative distribution functions (CDFs) (Majure et al., 1995). Thus, the technology that we are describing can provide a platform for many additional graphical methods.

3 The Link between ArcView 2.0 and XGobi

Since the features provided by the unidirectional link between ARC/INFO and XGobi (Symanzik et al., 1994) were useful but limited, it was natural to establish a bidirectional link between the much more flexible ArcView 2.0 and XGobi. This link utilizes Remote Procedure Calls (RPCs), an interprocess communications feature available in ArcView 2.0. The use of RPCs is a programming technique where a process on the local system (i. e., the client) invokes a procedure on a remote system (i. e., the server). In this context, the term request is used to refer to the client's desire to execute a particular remote procedure, and the term response is used for the result produced by the remote procedure (Stevens, 1990).

ArcView 2.0 allows RPCs and it also enables external programs to invoke internal ArcView 2.0 functions via RPCs. Within this environment XGobi has been adapted to the subroutine template code provided with the XGobi source code, which previously has been used for the implementation of the XGvis software system (Littman et al., 1992) and for our previous link between ARC/INFO and XGobi.

ArcView 2.0 has been customized for this application using ArcView 2.0's Avenue programming language. Virtually all of the default ArcView 2.0 functionality is available, plus several operations that deal only with the link. Specifically, ArcView 2.0 has been modified to do the following: initiate an RPC server and client, initiate and pass data to the XGobi process, brush points and request XGobi to brush the corresponding points, and process requests from XGobi to brush points. This functionality can be described in the following pseudo code:

```
repeat
  wait for action
  case action {
    when ARCVIEW_2.0 request:
      process request
    when START_LINK request:
      initiate the XGobi process
      init ArcView 2.0 as RPC server
      init ArcView 2.0 as RPC client (i.e., connect to
        XGobi RPC server)
      send RPC request to XGobi containing the data to
        be input into XGobi
      activate appropriate GUI control buttons
    when STOP_LINK request:
      send RPC request to XGobi to shut down
      shut down RPC server
      shut down RPC client
      deactivate appropriate GUI control buttons
    when BRUSH_POINTS request:
      change the color/glyph/size of specified points
      send RPC request to XGobi to brush corresponding points
    when RPC request from XGobi:
      change the color/glyph/size of specified points
  }
until (ArcView 2.0 QUIT request)
```

Both, ArcView 2.0 and XGobi have been set up as a server for RPCs as well as a client for RPCs. This allows ArcView 2.0 (as a client) to access the functionality added to XGobi (the server). The XGobi remote procedures callable from within ArcView 2.0 can be grouped into two classes. One class provides functions to transfer multivariate attribute data and new brushing (or subsetting) information into XGobi. For example, when ArcView 2.0 makes an RPC to an XGobi function called `RPC_Update_All_Symbols` providing new colors and glyphs for all points in the data set, XGobi will change the view according to the submitted values when processing this

RPC request. The other class contains functions that allow the calculation, drawing, addition, and deletion of different types of spatial CDFs. See Majure et al. (1995) for an example of the use of these functions.

It is not possible to give XGobi the full functionality of an RPC server that automatically processes all requests from its clients since such an automation would never terminate and thus, no user action within XGobi could be processed any more. Instead, a working procedure, that is a routine that runs once whenever the X Window System event loop finds no event, has been added to XGobi to check for incoming RPC requests from clients (namely ArcView 2.0) and to process these requests.

On the other hand, XGobi (as a client) sends requests to ArcView 2.0 (the server), asking for the update of the ArcView 2.0 view in accordance with the brushing and subsetting information of points within XGobi where this information has been altered. The modified XGobi can be described via the following pseudo code:

```
init XGobi as RPC server
init XGobi as RPC client
init XGobi defaults
repeat
  wait for action
  case action {
    when RPC request:
      execute appropriate function (i.e., update XGobi
        structures, data sets, and views)
      return response (success or fail) to client
    when user action:
      process user action
      if (user action = Move_Brush_Symbol)
        make RPC call (i.e., submit brushing information)
        wait for response (success or fail) from server
        if (fail)
          print warning
  }
until (RPC request = Quit_XGobi)
shutdown RPC server
exit
```

4 Security and Concurrency

In our link between ARC/INFO and XGobi (Symanzik et al., 1994), there was no particular need to consider security and concurrency issues. Since the link was only unidirectional, allowing XGobi clients to read (but not to write) data from the ARC/INFO data base through an intermediate process residing on the server's site, there was no requirement to implement security features such as authentication handles. Thus, this link allowed every user anywhere on the Internet to read data from an ARC/INFO data base at the server's site as long as the intermediate process was running. Today, it is common practice to allow unrestricted read access to selected data bases, e. g., through the World Wide Web.

The only concurrency aspect that had to be handled in the link between ARC/INFO and XGobi was a simultaneous update of all XGobi clients after modifications of the ARC/INFO data base. This problem was solved through the forking of child processes identical to the intermediate process. Each of these child processes communicates with one XGobi client, thus establishing one–to–one connections between server processes and XGobi clients.

However, in our current bidirectional link between ArcView 2.0 and XGobi, security and concurrency issues are much harder to address. Unfortunately, an ArcView 2.0 RPC server supports only one function: "1 – script execution – executes the given script and returns a string representation of the last object referenced or produced during the execution of the script" (Environmental Systems Research Institute, Inc., 1995). A string containing an Avenue script is required as an argument for the script execution. This string can be anything from a single Avenue statement through the complete text of an Avenue script. Just imagine that in the valid Avenue script `system.execute("ls")` the letters `ls` are exchanged by something else. Thus, there is no protection against the manipulation or deletion of entire ArcView 2.0 data bases or any of the analyst's files by an external user connected to the running ArcView 2.0 RPC server, hence a total lack of data security!

We have suggested that ESRI provide an RPC mechanism for Unix and/or DES (Data Encryption Standard) authentication in addition to the current default null authentication with their next ArcView upgrade. Unix authentication causes the transmission of additional fields (such as a time stamp, the name of the local host, the client's effective user and group IDs) with every RPC request. DES authentication promotes secure exchange of data in a standard fashion since it encrypts/decrypts data through public and private keys associated with the effective user ID of the calling process. For both types of authentication only valid requests are granted. Since XGobi is started from within ArcView 2.0 in this link, in case of the Unix authentication it seems to be reasonable to define valid requests as requests where local host and user ID match between client and server.

The concurrency issue (What happens if at least two XGobi processes provide different update information to ArcView 2.0 at the same time?) has been solved by a built–in feature of XGobi. Only one XGobi process, the one invoked from within ArcView 2.0, provides the features of an RPC server and RPC client. The other XGobi processes that have been cloned are "regular" XGobi processes that do not support RPCs. All XGobi processes (the one invoked from within ArcView 2.0 and the cloned ones) communicate to each other through the production and consumption of XEvents. When points are brushed or subsetted, an appropriate XEvent is generated. Even if one XGobi process is delayed for a while,

it sequentially processes the XEvents that have been generated by other XGobi processes. Whenever the XGobi invoked from within ArcView 2.0 processes an XEvent related to brushing or subsetting, it requests ArcView 2.0 to update its view. Due to this one–to–one link and the serialization of the XEvents, the concurrency issue has been solved.

5 An Example

The geographic area under consideration in this example is the Lake Icaria watershed, located in southwest Iowa, near Corning. This area is predominantly agricultural, but also contains Lake Icaria State Park. The scene which is shown in the ArcView 2.0 view in Figure 1 was collected on April 22, 1990 by the SPOT earth observation satellite.

A sample of the pixels in the scene has been taken in order to conduct the analysis. This has been done because, even in an area as small as the one under consideration, the number of pixels in the entire scene is still over 300,000. This makes many types of analyses computationally intensive and time consuming. The sample taken is a systematic random sample (Cressie, 1993), in which an initial pixel in the lower–left–hand corner of the image has been chosen at random and additional pixels have been included each 10 rows (200m) in both the horizontal and vertical directions. This process yielded a random sample of 800 locations. These locations, marked with different glyphs (Xs, circles, and filled boxes), are also shown in the ArcView 2.0 view in Figure 1.

The data collected is the amount of incident electromagnetic radiation in a specific range, or band, of wavelengths. For each pixel in the area of the image, there is a datum for each of the three instruments on the SPOT satellite, expressed through the variables *Icariac1*, *Icariac2*, and *Icariac3*. In addition, the variable *Clust* has been added to the data set, containing the results of a hierarchical cluster analysis.

The lower left XGobi view shows the dot plot of *Clust* with two clusters being brushed. It becomes obvious that these points fall into two corners of the data triangle of the lower right XGobi view. The ArcView 2.0 view reveals that values marked with circles are located uniquely on lake locations while values marked with filled boxes relate to locations with active vegetation.

The next steps during an exploratory data analysis might involve the brushing of the third corner of the data triangle or the selection of points from the ArcView 2.0 view that are located on well–known terrain such as roads or buildings.

6 Future Work

As soon as available in ArcView, there will be an authentication mechanism added to this link. Future work also involves the extension of the link towards other statistical packages such as S – PLUS®. Moreover, since the generic work required to incorporate RPCs into XGobi already has been done, it should be quite easy to add other spatial methods such as variograms to the link, using mechanisms similiar to the incorporation of spatial CDFs.

Acknowledgements

Research related to this article was supported by an EPA EMAP grant under cooperative agreement # CR822919. The article has not been subjected to the review of the EPA and thus does not necessarily reflect the view of the agency and no official endorsement should be inferred. Symanzik's research was also partially supported by a German "DAAD–Doktorandenstipendium aus Mitteln des zweiten Hochschulsonderprogramms".

References

Anselin, L. and Getis, A. (1992). Spatial Statistical Analysis and Geographic Information Systems. *Annals of Regional Science*, 26:19–33.

Cook, D., Cressie, N., Majure, J., and Symanzik, J. (1994). Some Dynamic Graphics for Spatial Data (with Multiple Attributes) in a GIS. In Dutter, R. and Grossman, W., editors, *COMPSTAT 1994: Proceedings in Computational Statistics*, pages 105–119, Heidelberg. Physica–Verlag.

Cressie, N. A. C. (1993). *Statistics for Spatial Data (revised edition)*. Wiley, New York, NY.

Ding, Y. and Fotheringham, A. S. (1992). The Integration of Spatial Analysis and GIS. *Computers, Environment and Urban Systems*, 16:3–19.

Environmental Systems Research Institute, Inc. (1995). *ArcView 2.0 On–Line Help: RPCServer Page*. Redlands, CA.

Fotheringham, A. S. and Rogerson, P. (1993). GIS and Spatial Analytical Problems. *International Journal of Geographical Information Systems*, 7:3–19.

Haslett, J., Bradley, R., Craig, P., Unwin, A., and Wills, G. (1991). Dynamic Graphics for Exploring Spatial Data with Application to Locating Global and Local Anomalies. *The American Statistician*, 45(3):234–242.

Littman, M., Swayne, D. F., Dean, N., and Buja, A. (1992). Visualizing the Embedding of Objects in Euclidean Space. *Computing Science and Statistics*, 24:208–217.

Majure, J. J. (1995). A Spatio–Temporal Statistical Model of Pollutant Concentrations in Surface Waters. Master's thesis, Iowa State University, Department of Statistics, Ames, Iowa 50011.

Majure, J. J., Cook, D., Cressie, N., Kaiser, M., Lahiri, S., and Symanzik, J. (1995). Spatial CDF Estimation and Visualization with Applications to Forest Health Monitoring. *Computing Science and Statistics*, 27:to appear.

Openshaw, S. (1991). Developing Appropriate Spatial Analysis Methods for GIS. In Maguire, D. J., Goodchild, M. F., and Hind, D. W., editors, *Geographical Information Systems: Principles and Applications, vol. 1*, pages 389–402, London. Longman.

S–PLUS is a registered trademark of Statistical Sciences, Inc.



Figure 1: *ArcView 2.0 view linked with two XGobi views.*

Stevens, W. R. (1990). *UNIX Network Programming.* Prentice–Hall, Englewood Cliffs, NJ.

Swayne, D. F., Cook, D., and Buja, A. (1991). XGobi: Interactive Dynamic Graphics in the X Window System with a Link to S. In *ASA Proceedings of the Section on Statistical Graphics*, pages 1–8, Alexandria, VA. American Statistical Association.

Symanzik, J., Majure, J., Cook, D., and Cressie, N. (1994). Dynamic Graphics in a GIS: A Link between ARC/INFO and XGobi. *Computing Science and Statistics*, 26:431–435.